

**ALWAYS AT YOUR COMMAND** 

TriloG Pro Series / /

# **MODEL 3064**

**Direct Screw Drive Garage Door Opener** 



## Highlights

- Powerful, fast performance Patented direct screw drive rail combined with powerful 140 volt DC motor provides maximum power & an opening speed of 10.0" per second\*\* to quickly open even the heaviest doors.
- Soft Stop / Soft Start Control DC technology allows your door to begin and end its movement smoothly instead of abruptly whenever you operate it, creating less noise and less wear on the door.
- Dependability A Limited Lifetime warranty<sup>◊</sup> on the motor and screw drive rail shows how confident Genie is that your opener will perform when you need it to for years to come.
- Assembled in the U.S.A.

- Big Door Capable For use on residential sectional doors up to 14' high & one-piece doors up to 8' high.
- Maintenance-Free Direct Drive System Self-lubricating screw drive rail requires no maintenance under normal operating conditions.
- Power on Demand Refers to the ability of the opener to continually monitor the door's travel & deliver just the right amount of power for smooth & consistent movement.
- GenieSense™ Monitoring Automatic force profiling & diagnostic technology improves safety by stopping operation when significant changes occur.
- A GENIE-NET - Intelligent internal platform allows the opener to expand its capability with great optional accessories.



THE GENIE STORY: Genie has a rich history in developing garage door openers that feature reliability, strength, safety, security, and convenience. Since 1954, Genie has produced millions of openers that serve millions of satisfied homeowners every day of every year. Shouldn't you have one in your garage? Genie — Always at Your Command!



# Standard Equipment & Warranty













ACCESSORIES

Features & Benefits

### **POWER & CONTROL**

**DC Motor Smart Technology** – The 140 volt DC motor with its 1 HPc\* rating offers powerful performance. The DC motor also allows for Soft Start/Soft Stop control so the door begins & ends its travel smoothly instead of abruptly. This helps create less noise and less wear & tear on your door.

**Screw Drive Design** – Patented direct screw drive rail offers incredibly strong lifting force that allows the opener to lift residential sectional doors up to 14' high! By eliminating the gearbox used on belt & chain models, the screw drive design increases reliability since fewer parts means less chance for potential breakdown in the future.

**C-Channel Rail** – Strong rail design helps promote durability & safety. Also conceals the screw drive rod for better appearance.

**Speed** – The powerhead has an opening speed of 10.0 inches/second\*\* to get you on your way faster.

Safe-T-Beam® Non-Contact Reversing System – When objects pass through the infrared beam, the garage door automatically stops closing & reverses open without having to make physical contact with the door.

Intellicode® Access Security System – Genie's superior encryption technology prevents piracy of the radio signal that operates your door by always selecting a new code from billions of combinations each time the opener is operated.

Sure-Lock™ Control – Allows you to lock out remote controls & wireless keypad at any time for increased security – also known as a vacation lock. (Included with Intelligent & basic wall consoles.)

### CONVENIENCE

Motion Detector Lighting System – Integrated motion detector turns the lights on automatically when you enter the garage with the added benefits of increased safety & security. The two light sockets can use incandescent (100 watts maximum per bulb) or most CFL and LED light bulbs. Lights are positioned toward the inside of the garage instead of the door for light where it's needed most and will stay on four minutes once you exit the garage.

**Auto Seek Dual Frequency** – The internal system automatically uses either the 315 or 390 MHz frequency produced by the remote control or keypad to help ensure the opener responds regardless of potential nearby frequency interference, such as military base equipment.

Pre-Programmed Remote – Ready to use out-of-the-box with simple steps to change the programming if so desired.

HomeLink® & Car2U® Compatibility – Works with current & ALL previous versions of HomeLink or Car2U

**Genie Professional Line Ratings** TriloG Pro Series IntelliG°Pro Series \* \* \* \*

ReliaG°Pro Series \*\*















# Motion Detector Lighting

## Convenience Features

Put more magic in your Genie opener with these great accessories!

### Wireless Keypad

Mounts outside your door to give you keypad code access to your garage, which is great when you are outside without the remote control. Back-lit keypad lets you easily see the numbers & allows you to control up to three openers.



Choose a color for the flip-up cover that best complements your home.



White Grav

**Battery Back-Up Unit** 

No more unexpectedly getting locked outside the garage when the power goes out! Genie's battery back-up can operate a garage door up to 50 cycles in a 24-hour period after the initial power outage. \*\*\* Colorful LED lights show charge status.

**A GETUIE-NET**Network Adaptor

Genie-Net is the intelligent platform built into TriloG™ & IntelliG®

Pro Series openers. The Network Adaptor simply plugs into a port on the unit, giving your opener the ability to expand its capability to work with other great products. Look for this symbol 📤 to identify those accessories that work with Genie-Net!

### Closed Confirm® Remote

Answers the nagging question as you leave home, "Did I close the garage door?" Once it properly closes, the Closed Confirm remote emits a beep & a green light flashes an assuring confirmation. If the door does not close properly, a warning tone sounds & a red light flashes. Operating range up to 1,000 feet in line of sight to the door!



### **△** Intelligent Wall Console

The back-lit LCD touch screen provides for easy-to-read information, including date & time display. It also allows you to input service reminders & contact info for your Pro Dealer for easy referral, and will operate up to three openers.



### 6' Power Cord (3064H)

Genie openers come with a standard 4' power cord. However, if you need a couple extra feet for harder to reach outlets, then you want our 6' power cord Model 3064H.

YOUR GENIE PROFESSIONAL DEALER:

© 2015 The Genie Company. Genie, IntelliG, ReliaG, Safe-T-Beam, Intellicode, Closed Confirm and the Genie logo are registered trademarks and Genie-Net, TriloG and Sure-Lock are trademarks of GMI Holdings, Inc., d/b/a The Genie Company. Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation. HomeLink is a registered trademark of Gentex Corporation. Car2U is a registered trademark of Lear Corporation.

<sup>\*</sup> Horsepower comparable (HPc) designates this garage door opener meets Genie's lifting force specification for 1 horsepower garage door openers.

noisepower comparative for the suggested will slow with one-piece doors.

\*\*\* \( \text{O.5}\) inches per second. Speed will slow with one-piece doors.

\*\*\* One cycle is a complete open and close of the door, testing performed at room temperature.

\( \text{Limited non-transferable warranty. See Operation & Maintenance manual for details.} \)